



Brida Lap-Joint ANSI/ASME B16.5 Class 150 lbs

DIMENSIONES EN PULGADAS Y (MILÍMETROS)

Tamaño Nominal Tubería	Ø Exterior Ø	Mínimo Espesor ff	Ø Hub X	Longitud con Hub Y	Ø Mínimo Agujero B	Ø Radio R	Taladros			Ø Tornillo
							Ø K Centro Tal.	No. Tal.	Ø Tal. L	
1/2 (DN15)	3.5 (90)	0.44 (11.2)	1.19 (30)	0.62 (16)	0.9 (22.9)	0.12 (3)	2.38 (60.3)	4	5/8 (15.875)	1/2 (12.7)
3/4 (DN20)	3.88 (100)	0.5 (12.7)	1.5 (38)	0.62 (16)	1.11 (28.2)	0.12 (3)	2.75 (69.9)	4	5/8 (15.875)	1/2 (12.7)
1 (DN25)	4.25 (110)	0.56 (14.3)	1.94 (49)	0.69 (17)	1.38 (34.9)	0.12 (3)	3.12 (79.4)	4	5/8 (15.875)	1/2 (12.7)
1 1/4 (DN32)	4.62 (115)	0.62 (15.9)	2.31 (59)	0.81 (21)	1.72 (43.7)	0.19 (5)	3.5 (88.9)	4	5/8 (15.875)	1/2 (12.7)
1 1/2 (DN40)	5 (125)	0.69 (17.5)	2.56 (65)	0.88 (22)	1.97 (50)	0.25 (6)	3.88 (98.4)	4	5/8 (15.875)	1/2 (12.7)
2 (DN50)	6 (150)	0.75 (19.1)	3.06 (78)	1 (25)	2.46 (62.5)	0.31 (8)	4.75 (120.7)	4	3/4 (19.05)	5/8 (15.875)
2 1/2 (DN65)	7 (180)	0.88 (22.3)	3.56 (90)	1.12 (29)	2.97 (75.4)	0.31 (8)	5.5 (139.7)	4	3/4 (19.05)	5/8 (15.875)
3 (DN80)	7.5 (190)	0.94 (23.9)	4.25 (108)	1.19 (30)	3.6 (91.4)	0.38 (10)	6 (152.4)	4	3/4 (19.05)	5/8 (15.875)
3 1/2 (DN90)	8.5 (215)	0.94 (23.9)	4.81 (122)	1.25 (32)	4.1 (104.1)	0.38 (10)	7 (177.8)	8	3/4 (19.05)	5/8 (15.875)
4 (DN100)	9 (230)	0.94 (23.9)	5.31 (135)	1.31 (33)	4.6 (116.8)	0.44 (11)	7.5 (190.5)	8	3/4 (19.05)	5/8 (15.875)
5 (DN125)	10 (255)	0.94 (23.9)	6.44 (164)	1.44 (36)	5.69 (144.4)	0.44 (11)	8.5 (215.9)	8	7/8 (22.225)	3/4 (19.05)
6 (DN150)	11 (280)	1 (25.4)	7.56 (192)	1.56 (40)	6.75 (171.4)	0.5 (13)	9.5 (241.3)	8	7/8 (22.225)	3/4 (19.05)
8 (DN200)	13.5 (345)	1.12 (28.6)	9.69 (246)	1.75 (44)	8.75 (222.2)	0.5 (13)	11.75 (298.5)	8	7/8 (22.225)	3/4 (19.05)
10 (DN250)	16 (405)	1.19 (30.2)	12 (305)	1.94 (49)	10.92 (277.4)	0.5 (13)	14.25 (362)	12	1 (25.4)	7/8 (22.225)
12 (DN300)	19 (485)	1.25 (31.8)	14.38 (365)	2.19 (56)	12.92 (328.2)	0.5 (13)	17 (431.8)	12	1 (25.4)	7/8 (22.225)
14 (DN350)	21 (535)	1.38 (35)	15.75 (400)	3.12 (79)	14.18 (360.2)	0.5 (13)	18.75 (476.3)	12	1 1/8 (28.575)	1 (25.4)
16 (DN400)	23.5 (595)	1.44 (36.6)	18 (457)	3.44 (87)	16.19 (411.2)	0.5 (13)	21.25 (539.8)	16	1 1/8 (28.575)	1 (25.4)
18 (DN450)	25 (635)	1.56 (39.7)	19.88 (505)	3.81 (97)	18.2 (462.3)	0.5 (13)	22.75 (577.9)	16	1 1/4 (31.75)	1 1/8 (28.575)
20 (DN500)	27.5 (700)	1.69 (42.9)	22 (559)	4.06 (103)	20.25 (514.4)	0.5 (13)	25 (635)	20	1 1/4 (31.75)	1 1/8 (28.575)
24 (DN600)	32 (815)	1.88 (47.7)	26.12 (663)	4.38 (111)	24.25 (616)	0.5 (13)	29.5 (749.3)	20	1 3/8 (34.925)	1 1/4 (31.75)