



### Brida Lap-Joint ANSI/ASME B16.5 Class 600 lbs

DIMENSIONES EN PULGADAS Y (MILÍMETROS)

Tamaño Nominal Tubería	Ø Exterior O	Mínimo Espesor tf	Ø Hub X	Longitud con Hub Y	Ø Mínimo Agujero B	Ø Radio R	Taladros			Ø Tornillo
							Ø K Centro Tal.	No. Tal.	Ø Tal. L	
1/2 (DN15)	3.75 (95)	0.56 (14.3)	1.5 (38)	0.88 (22)	0.9 (22.9)	0.12 (3)	2.62 (66.7)	4	5/8 (15.875)	1/2 (12.7)
3/4 (DN20)	4.62 (115)	0.62 (15.9)	1.88 (48)	1 (25)	1.11 (28.2)	0.12 (3)	3.25 (82.6)	4	3/4 (19.05)	5/8 (15.875)
1 (DN25)	4.88 (125)	0.69 (17.5)	2.12 (54)	1.06 (27)	1.38 (34.9)	0.12 (3)	3.5 (88.9)	4	3/4 (19.05)	5/8 (15.875)
1 1/4 (DN32)	5.25 (135)	0.81 (20.7)	2.5 (64)	1.12 (29)	1.72 (43.7)	0.19 (5)	3.88 (98.4)	4	3/4 (19.05)	5/8 (15.875)
1 1/2 (DN40)	6.12 (155)	0.88 (22.3)	2.75 (70)	1.25 (32)	1.97 (50)	0.25 (6)	4.5 (114.3)	4	7/8 (22.225)	3/4 (19.05)
2 (DN50)	6.5 (165)	1 (25.4)	3.31 (84)	1.44 (37)	2.46 (62.5)	0.31 (8)	5 (127)	8	3/4 (19.05)	5/8 (15.875)
2 1/2 (DN65)	7.5 (190)	1.12 (28.6)	3.94 (100)	1.62 (41)	2.97 (75.4)	0.31 (8)	5.88 (149.2)	8	7/8 (22.225)	3/4 (19.05)
3 (DN80)	8.25 (210)	1.25 (31.8)	4.62 (117)	1.81 (46)	3.6 (91.4)	0.38 (10)	6.62 (168.3)	8	7/8 (22.225)	3/4 (19.05)
3 1/2 (DN90)	9 (230)	1.38 (35)	5.25 (133)	1.94 (49)	4.1 (104.1)	0.38 (10)	7.25 (184.2)	8	1 (25.4)	7/8 (22.225)
4 (DN100)	10.75 (275)	1.5 (38.1)	6 (152)	2.12 (54)	4.6 (116.8)	0.44 (11)	8.5 (215.9)	8	1 (25.4)	7/8 (22.225)
5 (DN125)	13 (330)	1.75 (44.5)	7.44 (189)	2.38 (60)	5.69 (144.4)	0.44 (11)	10.5 (266.7)	8	1 1/8 (28.575)	1 (25.4)
6 (DN150)	14 (355)	1.88 (47.7)	8.75 (222)	2.62 (67)	6.75 (171.4)	0.5 (13)	11.5 (292.1)	12	1 1/8 (28.575)	1 (25.4)
8 (DN200)	16.5 (420)	2.19 (55.6)	10.75 (273)	3 (76)	8.75 (222.2)	0.5 (13)	13.75 (349.2)	12	1 1/4 (31.75)	1 1/8 (28.575)
10 (DN250)	20 (510)	2.5 (63.5)	13.5 (343)	4.38 (111)	10.92 (277.4)	0.5 (13)	17 (431.8)	16	1 3/8 (34.925)	1 1/4 (31.75)
12 (DN300)	22 (560)	2.62 (66.7)	15.75 (400)	4.62 (117)	12.92 (328.2)	0.5 (13)	19.25 (489)	20	1 3/8 (34.925)	1 1/4 (31.75)
14 (DN350)	23.75 (605)	2.75 (69.9)	17 (432)	5 (127)	14.18 (360.2)	0.5 (13)	20.75 (527)	20	1 1/2 (38.1)	1 3/8 (34.925)
16 (DN400)	27 (685)	3 (76.2)	19.5 (495)	5.5 (140)	16.19 (411.2)	0.5 (13)	23.75 (603.2)	20	1 5/8 (41.275)	1 1/2 (38.1)
18 (DN450)	29.25 (745)	3.25 (82.6)	21.5 (546)	6 (152)	18.2 (462.3)	0.5 (13)	25.75 (654)	20	1 3/4 (44.45)	1 5/8 (41.275)
20 (DN500)	32 (815)	3.5 (88.9)	24 (610)	6.5 (165)	20.25 (514.4)	0.5 (13)	28.5 (723.9)	24	1 3/4 (44.45)	1 5/8 (41.275)
24 (DN600)	37 (940)	4 (101.6)	28.25 (718)	7.25 (184)	24.25 (616)	0.5 (13)	33 (838.2)	24	2 (50.8)	1 7/8 (47.625)