



Brida BS 3293 Tipo Slip-On Class 150 PSI

DIMENSIONES EN PULGADAS Y (MILÍMETROS)

Tamaño Nominal Tubería	Ø Exterior O	Ø Interior B1	No. De Taladros	Ø Tornillo	Ø Agujero Tornillo L	Ø Círculo Tal. D	Espesor C	Ø Diámetro final Hub X	Ø Lengitud Hub Y1	Ø Radio End Hub R
26	34.25	26.25	24	1.25	1.375	31.75	2	28.5	3 3/8	0.25
28	36.5	28.25	28	1.25	1.375	34	2.0625	30.75	3 4/9	0.25
30	38.75	30.25	28	1.25	1.375	36	2.125	32.75	3 1/2	0.25
32	41.75	32.25	28	1.5	1.625	38.5	2.25	35	3 5/8	0.3125
34	43.75	34.25	32	1.5	1.625	40.5	2.3125	37	3 2/3	0.3125
36	46	36.25	32	1.5	1.625	42.75	2.375	39.25	3 3/4	0.3125
38	48.75	38.25	32	1.5	1.625	45.25	2.375	41.75	3 3/4	0.375
40	50.75	40.25	36	1.5	1.625	47.25	2.5	43.75	3 7/8	0.375
42	53	42.25	36	1.5	1.625	49.5	2.625	46	4	0.375
44	55.25	44.25	40	1.5	1.625	51.75	2.6875	48	4	0.4375
46	57.25	46.25	40	1.5	1.625	53.75	2.6875	50	4	0.4375
48	59.5	48.25	44	1.5	1.625	56	2.75	52.25	4 1/8	0.4375